



enoline 4
REF



enoline 8
REF - WINE CARD

printed OCT. 2010

THE ENOLINE CLASSIC SERIES HAS GROWN TO BE THE BEST SELLER WORLDWIDE THANKS TO ITS VERSATILITY. IT IS AVAILABLE IN BOTH 4 OR 8 BOTTLE VERSIONS WITH A DEPTH OF 20 CM THAT MAKES IT ADAPTABLE TO ALL VENUES.

enoline

- Available models:
 - enoline 4 ref (4 bottles in a row)
 - enoline 8 rt / ref / clim / dual (8 bottles in a row)
- Wine temperature:
 - room temperature
 - refrigerated: from 7 to 18°C (from 45 to 65°F)
 - climate controlled: from 7 to 20 °C (from 45 to 68 °F)
 - dual: 4 chilled bottles + 4 climated bottles
- Use and system activation: behind the counter (without wine card) or self-service (with wine card).
- Gas supply: food nitrogen or argon (cylinder or generator non included).
- Servings: 1 or 3 volume membrane keys.
- Wine card type: chip card (SMART card).
- Display (wine card systems only): each bottle position has a 4 digit price display and a 16 character LCD display for general card information.
- Materials: stainless steel with baydur black polyurethane lid.
- Cooling system: by air compressor.
- Condensation drainage: required.
- Compressor positioning: right or left side.
- Lighting: with double led (static light).
- Bottles lifting system: pneumatic pistons which can be operated with air or nitrogen.
- Positioning: refrigerated and climated controlled models require to keep a 30 cm (12") distance from compressor side and 5 cm (2") from the rear.
- Modules interfacing: LAN network, TCP/IP protocol.

models	L	H	D	weight	electrical requirements
enoline 4 REF	29.5"	25.2"	8"	88.2 lbs	110 V. - 150 W.
enoline 8 RT	38.2"	25.2"	8"	99.2 lbs	110 V. - 30 W.
enoline 8 REF	47"	25.2"	8"	143.3 lbs	110 V. - 150 W.
enoline 8 CLIM	47"	25.2"	8"	143.3 lbs	110 V. - 150 W.
enoline 4+4 DUAL	47"	25.2"	8"	143.3 lbs	110 V. - 150 W.